



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx IMQ 14.0003X Issue No: 1 Certificate history:
Status: **Current** Page 1 of 4 [Issue No. 1 \(2016-10-26\)](#)
Date of Issue: **2016-10-26** [Issue No. 0 \(2014-05-06\)](#)

Applicant: **Bimed Teknik Aletler San. Ve Tic. A.Ş.**
S.S Bakır ve Piriç Sanayi Sitesi Leylak Caddesi No:15 Beylikdüzü
Istanbul
Turkey

Equipment: **Drain plug (model reference : BDRV...)**
Optional accessory:

Type of Protection: **Ex eb; Ex tb**

Marking: Ex eb IIC Gb
Ex tb IIIC Db IP66

*Approved for issue on behalf of the IECEx
Certification Body:*

Mr. Mauro CASARI

Position:

IMQ ExCB Manager

*Signature:
(for printed version)*

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the [Official IECEx Website](#).

Certificate issued by:

Istituto Italiano del Marchio di Qualità S.p.A
Via Quintiliano 43
20138 Milano,
Italy





IECEx Certificate of Conformity

Certificate No: IECEx IMQ 14.0003X Issue No: 1

Date of Issue: 2016-10-26 Page 2 of 4

Manufacturer: **Bimed Teknik Aletler San. Ve Tic. A.Ş.**
S.S Bakır ve Piriç Sanayi Sitesi Leylak Caddesi No:15 Beylikdüzü
Istanbul
Turkey

Additional Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2011 Edition:6.0	Explosive atmospheres - Part 0: General requirements
IEC 60079-31 : 2013 Edition:2	Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
IEC 60079-7 : 2015 Edition:5.0	Explosive atmospheres – Part 7: Equipment protection by increased safety "e"

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

[IT/IMQ/ExTR14.0003/01](#)

Quality Assessment Report:

[IT/CES/QAR12.0003/03](#)

[IT/CES/QAR12.0003/02](#)



IECEX Certificate of Conformity

Certificate No: IECEx IMQ 14.0003X

Issue No: 1

Date of Issue: 2016-10-26

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

Drain plug BDRV... is a device intended for use to evacuate the water generated because of condensation inside the enclosure. Due to the fact that water is accumulated in bottom part of the enclosure, "drain plug" is assembled in the lowest part of the enclosure. As a principle, no extra pressure is needed to drain the water out of the enclosure. Water will come out with the presence of drain plug device. Drain plug membrane is manufactured from sintered material: only brass can be used as raw material. The drain plug body is generally made in brass or, as alternative, in stainless steel (in case of ambient temperature below -30°C , must be used austenitic steels or brass).

CONDITIONS OF CERTIFICATION: YES as shown below:

- The interfaces between the valve and associated enclosures is made by threaded joint: it is the user's responsibility to ensure that the appropriate ingress protection degree is maintained, carrying out the installation according to safety manufacturer instructions.
- The temperature class will be dependent on the enclosure into which it is installed, taking into account that at their point of mounting, these devices are approved for use at the following working temperature:
 $-60 \div 85^{\circ}\text{C}$.
- Plain holes shall be no larger than 0,7mm above the major diameter of the drain valve thread and the device shall be secured with a locknut.



IECEx Certificate of Conformity

Certificate No: IECEx IMQ 14.0003X

Issue No: 1

Date of Issue: 2016-10-26

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

New standard applied, below mechanical change of product:

- The hole on the side of the cap is removed, and moved to the side, and the hole diameter is smaller.
- The name of the product is changed in "drain plug" instead "drain valve"
- Change from "U" to "X"

Annex:

[IECEx IMQ 14.0003X issue No. 1 Annex.pdf](#)


General description

Drain plug BDRV... is a device intended for use to evacuate the water generated because of condensation inside the enclosure.

Due to the fact that water is accumulated in bottom part of the enclosure, “drain plug” is assembled in the lowest part of the enclosure. As a principle, no extra pressure is needed to drain the water out of the enclosure. Water will come out with the presence of drain plug device. Drain plug membrane is manufactured from sintered material. For the selection of sintered material, working temperature, chemical resistance, aging conditions and atmospheric structure are taken into consideration: only brass can be used as raw material.

The drain plug body is generally made in brass or, as alternative, in stainless steel (in case of ambient temperature below -30°C, must be used austenitic steels or brass).

Type code as below:



Specific conditions of use “X”

- The interfaces between the valve and associated enclosures is made by threaded joint: it is the user’s responsibility to ensure that the appropriate ingress protection degree is maintained, carrying out the installation according to safety manufacturer instructions.
- The temperature class will be dependent on the enclosure into which it is installed, taking into account that at their point of mounting, these devices are approved for use at the following working temperature:
-60 ÷ 85 °C.
- Plain holes shall be no larger than 0,7mm above the major diameter of the drain valve thread and the device shall be secured with a locknut.

Annex to: IECEx IMQ 14.0003X issue No. 1
Applicant: Bimed Teknik Aletler San. Ve Tic. A.Ş.
Apparatus: BDRV ...



Design options

Materials: stainless steel, brass for body, silicone for o-ring, brass for membrane.

Threads types: N – NPT ANSI ASME B.1.20.1
M - ISO pitch 1,5 (EN 60423)

Sizes:

Type	Model
BDRV ...	BDRV 1 M .
	BDRV 1 N .
	BDRV 2 M .
	BDRV 2 N .

Manufacturer's Documents

Proper details to the use on installation and use of equipments are listed in Safety, Maintenance and Mounting Instructions – Drain Plug BDRV (**MI-DV** rev. 1 dated 2016.07.19).